


| Main Specification    |          |          | Image space NA      | 0.1     |
|-----------------------|----------|----------|---------------------|---------|
| Magnification         | 0.192X   | 0.155X   | 0.118X              | 0.01    |
| Working Distance      | 530.3±5  | 651.1±5  | 845.7±5             | 2158    |
| Conjugate Distance    | 671.8±9  | 792.6±9  | 987.2±9             | 42.87   |
| Flange Focal Distance | 465±0.5  |          | Exit pupil diameter | 22.27   |
| Max image circle      | ø64      |          | Exit pupil position | -107.16 |
| FNø.                  | 4.0-16   |          |                     |         |
| EFL                   | 90       |          |                     |         |
| Distortion            | 0.05%    |          |                     |         |
| IMAGE QUALITY         |          |          |                     |         |
| AXIS                  | ø46.2    | ø66      |                     |         |
| 200lp/mm              | 125lp/mm | 125lp/mm |                     |         |

注：  
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:  
LINEARITY TOLERANCES ±0.05  
ANGULAR TOLERANCES ARE ±30°  
DRAFT ANGLES AREA ±0.5°/SIDE



| 设计 | 校对 | 审核 | 批准 | 名称           | 材料(环保) | 单位 | 比例  |
|----|----|----|----|--------------|--------|----|-----|
|    |    |    |    | MF9015A规格书   | -      | MM | 1:1 |
|    |    |    |    | MF9015A-SPEC |        |    | 1/1 |
|    |    |    |    |              |        |    | 版本  |
|    |    |    |    |              |        |    | V0  |