



Main Specification		WD	Magnification
Working Distance	150-5000	200	-0.172X
Magnification Range	0.17X-0.005X	220	-0.132X
Max image	φ30	250	-0.107X
F.NO	F=2.8-16	300	-0.09X
FEL	28±5%	400	-0.068X
FOV(D)	55°	500	-0.055X
Flange Focal Distance	12	600	-0.046X
ENP Diameter	φ9.96	800	-0.035X
Distortion	<0.3%	1000	-0.028X
Rel.ill	>69%	1500	-0.019X
Dimensions	φ54×96.87	2000	-0.014X
Filter screw size	M4.9X P0.75	3000	-0.009X
Mount	M4.2XP1.0	5000	-0.006X

标注	处数	更改文件号	担当	变更日期	批准
1	1	LS04.028A20220314.01	设计	2021.10.12	
2	1	LS04.028A2022110201	校对	2021.10.12	
3	1	LS04.028A2022110201	审核	2021.10.12	
4	1	LS04.028A2023083101	批准	2023.08.31	

TOLERANCE:  
LINEARITY TOLERANCES ±0.05  
ANGULAR TOLERANCES ARE ±30°  
DRAFT ANGLES AREA±0.5°/SIDE



材料(环保)	---	单位	MM	比例	1:1
名称	LS04.028A规格书	页码	1/1	版本	V06
代号	LS04.028A-SPEC				