



Main Specification		W/D	Magnification
Working Distance	220-5000	220	-0.461X
Magnification Range	0.46X-0.02X	250	-0.394X
Max image	φ30	300	-0.317X
F.NO	F=2.8-16	400	-0.227X
EFL	80±5%	500	-0.177X
FOV(D)	19.5°	600	-0.145X
Flange Focal Distance	12	800	-0.106X
ENP Diameter	φ28.5	1000	-0.084X
Distortion	<0.2%	1500	-0.055X
Rel.Ill	>78%	2000	-0.041X
Dimensions	φ62×112	3000	-0.027X
Filter screw size	M58XP0.75	5000	-0.016X
Mount	M4.2XP1.0		

标记	处数	更改文件号	担当	变更日期	批准
△6	整体	LS04.080A.2023.083.001		2023.08.31	
△5	整体	LS04.080A.2022.018.001		2021.01.18	
△4	整体	LS04.080A.2022.013.001	设计	2021.01.13	
△3	整体	LS04.080A.2021.012.001	校对	2021.10.12	
△2	整体	LS04.080A.2021.072.001	审核	2021.7.20	

TOLERANCE:  
LINEARITY TOLERANCES ±0.05  
ANGULAR TOLERANCES ARE ±30°  
DRAFT ANGLES AREA±0.5°/SIDE



材料(环保)	单位	比例
---	MM	1:1
LS04.080A规格书		页码
		1/1
LS04.080A-SPEC		版本
		V06